



## **NoTile™ Questions and Answers**

### **WHAT ARE NOTILE™ PANELS MADE FROM?**

NoTile™ panels are made from glass fibre reinforced polyester (GRP) and the colour-carrying layer (the Gelcoat) contains the silver antimicrobial.

### **WILL THE GROUT LINES GO BLACK WITH MOULD?**

No. NoTile™ panels are completely different to traditional ceramic products and cannot support the growth of mould because the surface is not porous as is traditional grout and the surface includes a silver antimicrobial.

### **WHAT COLOURS ARE AVAILABLE?**

White is traditionally held in stock. Any British Standard or RAL colour is available, we can also colour match upon request, however, the grout line will be the same colour as the tiles

### **WHAT PATTERNS ARE AVAILABLE?**

There are three standard styles of tile; a 200 x 200mm tile; a 152 x 152mm tile and a 330 x 250mm vertical tile. The tile style will determine the size of the sheet. If the volumes are high enough CFM Ltd will manufacture a new design for the client.

### **WHAT SIZES ARE AVAILABLE?**

200 x 200mm: 2400 x 1795mm (nominally)

200 x 200mm: 2600 x 1795mm (nominally)

152 x 152mm: 2455 x 1224mm (nominally)

330 x 250mm: 2645 x 1750mm (nominally)

Panel sizes can be modified during manufacture or cut to size in our own factory.

### **HOW ARE THE PANELS FASTENED TO THE WALLS?**

These very flexible panels can be easily fixed to plaster, wood, brick and old tiles using a “grab adhesive”. New plaster will need to be sealed. We can supply the adhesive or recommend an alternative.

### **WHAT DO WE DO ABOUT THE JOINTS?**

The preferred method is to fill the joints with gelcoat. This provides a clean continuous membrane rather than visual joints. We supply a jointing kit with all orders. We do not supply jointing strips however they can be used as an alternative.

### **DO YOU FIT?**

No. We only supply the panels; however, on large jobs we can offer a site visit with demonstration. Each order is sent with full fitting and jointing instructions and we are always happy to discuss fitting and jointing over the phone.

\*Please call us anytime to discuss any further queries\*